

















LIOHTWELL®

HiGen Driverless LED High Bay













PRODUCT FEATURES

- ✓ High thermal efficient aluminium heatsink with stereoscopic ventilation
- The latest LED technology and design for performance & durability
- IP65 rated with waterproof and dust-proof breathable film
- Energy savings & reduced maintenance over HID high bays
- Environmentally friendly: no mercury or hazardous substances

Application

Factory lighting, Stockroom lighting, Assembly lighting, Retail lighting, Sports center lighting, Petrol station lighting, Supermarket lighting, Stadium lighting, School lighting

PRODUCT SPECIFICATION

Code	Dimensions	Lumens	Power	Voltage	LED	сст	CRI	Beam	IP	Material	Dimmable
HBDL/60W/PEN/CWND	ø 255*160mm	6480	60W	AC110-305V	Philips 3030	6000K	>80	120°	IP65	Aluminium	No
HBDL/100W/PEN/CWND	ø 295*175mm	10800	100W	AC190-260V	Philips 3030	6000K	>80	120°	IP65	Aluminium	No
HBDL/150W/PEN/CWND	ø 335*175mm	16200	150W	AC190-260V	Philips 3030	6000K	>80	120°	IP65	Aluminium	No
HBDL/200W/PEN/CWND	ø 375*175mm	21600	200W	AC190-260V	Philips 3030	6000K	>80	120°	IP65	Aluminium	No